



## PRODUCT SPECIFICATION

SPECIFICATION

### Product Name

## TÜRBİN YAĞI 100 / TURBIN AND CIRCULATION OIL 100

PRIMARY TESTS	METHOD	SPECIFICATION		
		MIN	TYP	MAX
Appearance	Visual		Clear and Bright	
Colour	ASTM D1500 / TS 1713 ISO 2049	1	2	3
Density 15°C, g/ml	ASTM D4052 / TS EN ISO 12185	0,880	0,890	0,910
Viscosity 40 °C, mm <sup>2</sup> /s	ASTM D445 / TS EN ISO 3104	90	100	110
Determination of water	ASTM D2711 / TS 13409			
- Free water, ml		30		
- Emulsion, ml				2
- Water in oil, %				0,5
Foaming Chactaristics (I,II,III Kd.) ml/ml	ASTM D892 / TS 1834 ISO 6247	100/0	100/0	100/0
Solid Particle Content	TS ISO 4406			-/17/14

SECONDARY TESTS	METHOD	SPECIFICATION		
		MIN	TYP	MAX
Viscosity 100 °C, mm <sup>2</sup> /s	ASTM D445 / TS EN ISO 3104	10,5	11	11,5
Viscosity Index	ASTM D2270 / TS ISO 2909	95		
Pour Point, °C	ASTM D97 / TS EN ISO 3016			- 12
Flash Point, °C (COC)	ASTM D92 / TS EN ISO 2592	236		
Copper Corrosion (100°C, 3 h)	ASTM D130 / TS 2741 EN ISO 2160			1
Rust Test ( Process B )	ASTM D665 / TS 6830 ISO 7120		Pass	
Water Content %m/m	ASTM D95 / TS 6147 EN ISO 12937			0,02
Acid Number, mgKOH/g	ASTM D974 / TS 9178 ISO 6618			0,2
Determination of air, 75°C, min.	TS 5768 ISO 9120			18

**PERFORMANCE LEVELS :** DIN 51515 ( R+O ), BS 489, MIL-L-17672 D

\* As the defined values are typical values, there can be some little changes according to the production. M Oil keeps all the rights to update and change the formulations of products without making any announcements. For the updated informations and technical datas about the products and product packagings, please contact with M Oil.