



PRODUCT SPECIFICATION

SPECIFICATION

Product Name: **ATF CVT**

PRIMARY TESTS	METHOD	SPECIFICATION		
		MIN	TYP	MAX
Appearance	Visual	Clear and Bright		
Colour		1.0	L 1.5	2.5
Density 15 °C, g/ml	ASTM D4052 / TS EN ISO 12185	0.830	0.850	0.870
Viscosity 100 °C, mm ² /s	ASTM D445 / TS EN ISO 3104	6	7.1	8.5
Viscosity 40 °C, mm ² /s	ASTM D445 / TS EN ISO 3104	30	35	50
Viscosity Index	ASTM D2270 / TS ISO 2909	165	170	
Foaming Characteristic (I,II,III Kd.) ml/ml	ASTM D892 / TS 1834 ISO 6247	(50/0, 50/0, 50/0)		

SECONDARY TESTS	METHOD	SPECIFICATION		
Pour Point, °C	ASTM D97 / TS EN ISO 3016			-40
Flash Point, °C (COC)	ASTM D92 / TS EN ISO 2592	210		
Burning Point °C (COC)	ASTM D92 / TS EN ISO 2592	230		
Copper Corrosion (100 °C, 3 hours)	ASTM D130 / TS 2741 EN ISO 2160			2
Rust Test	ASTM D665 / TS 6830 ISO 7120		Pass	

Performance Levels : BMW P/N 83 22 0 136 376, 83 22 0 429 154, EZL799, EZL 799A; Punch EZL 799, EZL 799A; CHRYSLER MOPAR CVTF+4, 05191184AA; DAIHATSU AMMIX CVTF DTC, CVTF D FE; DODGE/JEEP NS-2; FORD MERCON, CVT23, CFT30, WSS-M2C933-A, XT-7-QCFT; GM DEX-CVT Fluid, ACDelco CVT Fluid P/N 19260800, CVTF I-Green2; HONDA CVTF, 08200 9006, HMMF (without starting clutch), Genuine HCF 2 Transmission Fluid 08200 HCF2; HYUNDAI/KIA SP CVT 1; MAZDA CVTF 3320; MB CVT28, MB 236.20; MINI 83 22 0 136 376, EZL 799, EZL 799A, ZF CVT V1; MITSUBISHI Diamond Queen CVTF J1, CVTF-J4; NISSAN NS-1, CVT Fluid NS-2, NS-3, Matic W; RENAULT ELFMATIC; SATURN 22688912, SHELL Green 1V; SUBARU CVTF for Lineartronic, K0425Y0710, High Torque CVT K0421Y0700, Lineartronic II, K0425Y0711, e-CVTF, i-CVTF, CV-30; SUZUKI CVT Fluid Green 1, Green 2, NS-2, VTF 3320, TC; TOYOTA Genuine CVTF TC, CVTF FE; VW/AUDI G 052 180 (-A2), G 052 516 A2

Document Code	Revision No/Date	Page No	Prepared	Checked	Approved
KG-ÜS-219	00/04.03.2026	1/1	LAB. & QUALITY SPECIALIST	MANAGEMENT REPRESENTATIVE	FACTORY MANAGER

* As the defined values are typical values, there can be some little changes according to the production. M Oil keeps all the rights to update and change the formulations of products without making any announcements. For the updated informations and technical data about the products and product packagings, please contact with M Oil.