



## PRODUCT SPECIFICATION

SPECIFICATION

### Product Name

# KIZAK YAĞI 68 / SLIDEWAY OIL 68

PRIMARY TESTS	METHOD	SPECIFICATION		
		MİN	TYP	MAX
Appearance	Visual		Clear and Bright	
Colour	ASTM D1500 / TS 1713 ISO 2049	2	2,5	3,5
Density 15°C, g/ml	ASTM D4052 / TS EN ISO 12185	0.870	0.880	0.900
Viscosity 40 °C, mm <sup>2</sup> /s	ASTM D445 / TS EN ISO 3104	61,2	68	74,8
Water Separation 54°C, minute	ASTM D1401 / TS 6122 ISO 6614			40
Solid Particle Content	TS ISO 4406			21/19/15

SECONDARY TESTS	METHOD	SPECIFICATION		
		MİN	TYP	MAX
Viscosity 100 °C, mm <sup>2</sup> /s	ASTM D445 / TS EN ISO 3104		8.7	
Viscosity Index	ASTM D2270 / TS ISO 2909	90		
Pour Point, °C	ASTM D97 / TS EN ISO 3016			-12
Flash Point, °C (COC)	ASTM D92 / TS EN ISO 2592	230		
Rust Test	ASTM D665 / TS 6830 ISO 7120		Pass	
Neutralization number mgKOH/g	ASTM D974 / TS 9178 ISO 6618			2
Copper Corrosion (100°C, 3 hours)	ASTM D130 / TS 2741 EN ISO 2160			2

**PERFORMANCE LEVELS :** Cincinati Milacron P-47, P-50

\* As the defined values are typical values, there can be some little changes according to the production. M Oil keeps all the rights to update and change the formulations of products without making any announcements. For the updated informations and technical datas about the products and product packagings, please contact with M Oil.