



# PRODUCT SPECIFICATION

## SPECIFICATION

Product Name: **BRAKE FLUID DOT 4**

| PRIMARY TESTS                        | METHOD                       | SPECIFICATION    |      |      |
|--------------------------------------|------------------------------|------------------|------|------|
|                                      |                              | MIN              | TYP  | MAX  |
| Appearance                           | Visual                       | Clear and Bright |      |      |
| Colour                               |                              | Yellow           |      |      |
| Density 15 °C, g/ml                  | ASTM D4052 / TS EN ISO 12185 | 1.03             | 1.04 | 1.08 |
| Viscosity 100 °C, mm <sup>2</sup> /s | ASTM D445 / TS EN ISO 3104   | 1.5              |      | 4.0  |
| Boiling Point, °C                    | TS 3582                      | 230              |      |      |

**PERFORMANCE LEVELS:** SAE J 1703, 1704, FMVSS 116, DOT 4, ISO 4925

| Document Code | Revision No/Date | Page No | Prepared                    | Checked                   | Approved        |
|---------------|------------------|---------|-----------------------------|---------------------------|-----------------|
| KG-ÜS-107     | 07/11.08.2025    | 1/1     | FACTORY HSEQ & LAB. MANAGER | MANAGEMENT REPRESENTATIVE | FACTORY MANAGER |

\* As the defined values are typical values, there can be some little changes according to the production. M Oil keeps all the rights to update and change the formulations of products without making any announcements. For the updated informations and technical data about the products and product packagings, please contact with M Oil.