



PRODUCT SPECIFICATION

SPECIFICATION

Product Name

MOTORLU AĞAÇ TESTERESİ ZİNCİR YAĞI MOTORIZED TREE SAW CHAIN OIL

PRIMARY TESTS	METHOD	SPECIFICATION		
		MİN	TYP	MAX
Appearance	Visual	Clear and Bright		
Colour	ASTM D1500 / TS 1713 ISO 2049	L 0,5	1	2,5
Density 15'C, g/ml	ASTM D4052 / TS EN ISO 12185	0.875	0.885	0.905
Viscosity 100 'C, mm ² /s	ASTM D445 / TS EN ISO 3104	10.4	11	12.5
Viscosity 40 'C, mm ² /s	ASTM D445 / TS EN ISO 3104	90	100	110
Viscosity Index	ASTM D2270 / TS ISO 2909	93		

SECONDARY TESTS	METHOD	SPECIFICATION		
Pour Point, 'C	ASTM D97 / TS EN ISO 3016			- 6
Flash Point, 'C (COC)	ASTM D92 / TS EN ISO 2592	240		
Burning Point 'C (COC)	ASTM D92 / TS EN ISO 2592	260		
Copper Corrosion (100'C, 3 hours)	ASTM D130 / TS 2741 EN ISO 2160			1

PERFORMANCE LEVELS : API : SA / CA

* As the defined values are typical values, there can be some little changes according to the production. M Oil keeps all the rights to update and change the formulations of products without making any announcements. For the updated informations and technical datas about the products and product packagings, please contact with M Oil.