

TÜRBİN YAĞI 150

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

Date of First Publication : 20.12.2003 Revision Date : 28.11.2020 **Revision Number** : 07 : KG-F-244 SDS Number

Page 1 of 9

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / **UNDERTAKING**

1.1 Product identifier	TÜRBİN YAĞI 150
1.2 Relevant identified uses of the substance or mixture and uses advised against	Identified uses: Industrial oil
1.3 Details of the supplier of the safety data sheet	GÜZEL ENERJİ AKARYAKIT A.Ş. 10013 Sokak No: 6 A.O.S.B. Çiğli / İZMİR Tel: 0 232 328 10 36 Faks: 0 232 328 20 82 e-mail : moillaboratuvar@oyakpetrol.com.tr
1,4 Emergency telephone number	Güzel Enerji Akaryakıt A.Ş. : 0 232 328 10 36 UZEM (National Poison Consultancy Center): 114

SECTION 2 : HAZARD IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Not Classified

2.2 Label elements

No Label elements according to Regulation (EC) No 1272/2008

Signal Words : No marker words

2.3 Other hazards

Physical / Chemical Hazards : Not classified as harmful

Health Hazards : Not classified as harmful

Environmental Hazards : Not classified as harmful



TÜRBİN YAĞI 150

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

Date of First Publication: 20.12.2003Revision Date: 28.11.2020Revision Number: 07SDS Number: KG-F-244

Page 2 of 9

SECTION 3 : COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substances

Not Applicable

3.2 Mixtures

Highly refined base oil (IP 346 DMSO extraction, <3%). Special performance additives.

Chemical Composition	CAS No	EC No	Concentration	Classification
Solvent naphtha (petroleum), heavy aromatic	64742-94-5	265-198-5	< %0,5	STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Alkyl phenol	-	-	< %0,2	Skin Irrit.2, H315 Aquatic Chronic 1, H410

Additional information:

The Full Text for all Hazard Statements are Displayed in Section 16

/

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

EYE CONTACT : Wash thoroughly with plenty of water. Remove any contact lenses. Obtain medical advice if any pain or redness develops or persists.

SKIN CONTACT : Wash skin thoroughly with soap and plenty water. Remove heavily contaminated clothing and wash underlying skin.

INHALATION: If inhalation of mists, fumes or vapour causes irritation to the nose or throat, or coughing, remove to fresh air. If symptoms persist, obtain medical advice.

INGESTION: If contamination the mouth occurs, wash out thoroughly with water. If ingestion occurs large amounts, do not induce vomiting; obtain medical advice of.

4.2 Most important symptoms and effects, both acute and delayed

Ingestion may result in nausea, vomiting and/or diarrhoea

4.3 Indication of any immediate medical attention and special treatment needed

Notes to doctor/physician: Treat symptomatically



TÜRBİN YAĞI 150

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

Date of First Publication: 20.12.2003Revision Date: 28.11.2020Revision Number: 07SDS Number: KG-F-244

Page 3 of 9

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Dry chemical powder, foam, water fog, CO2

Unsuitable extinguishing media : Do not interfere with water to fire. Throwing strong water may spread fire.

5.2 Special hazards arising from the substance or mixture

Combustion occurs as a result of toxic gases. Carbon monoxide may be evolved if incomplete combustion occurs. With high temperatures may burn.

5.3 Advice for firefighters

Closed areas, by trained personnel using fire protective clothing and oxygen mask deflated.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Safety glasses, work clothes, boots, gloves and boots should be used. Provide adequate ventilation

6.2 Environmental precautions

Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground.

Local authorities should be advised if significantspillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Slippery when spilt. Scrape up bulk of solid material and remove liquid with sand or other suitable inert absorbent material. Spilled product should be isolated from sources of ignition, good ventilation should be provided. Recovery of large spillages should be done by specialist personel.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.



TÜRBİN YAĞI 150

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

Date of First Publication: 20.12.2003Revision Date: 28.11.2020Revision Number: 07SDS Number: KG-F-244

Page 4 of 9

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Good ventilation should be provided in the environment and should be avoided during use of the inhalation. Skin contact should be avoided and hygienic rules should be applied. Avoid eating, drinking and smoking while using. Wash hands thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Store in tightly-closed, original container in a dry, cool and well-ventilated place. Be exposed to direct sun rays, should not be stored near heat sources.

7.3 Specific end use(s)

Not applicable

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure Limit Values: Base oil – uncertain TWA: 5 mg/m³ 8 hour

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Provide adequate ventilation in the work area. Avoid inhalation of vapours.

8.2.2 Individual protection measures, such as personal protective equipment

Eye protection

If contact is likely safety glasses with side shields are recommended.

Skin protection

Wear protective clothing and gloves.

Hand protection

Chemical-resistant gloves (nitrile or neoprene) should be used.

Respiratory protection

If operations are such that exposure to vapour mis tor fume may be anticipated then suitable approved respiratory equipment should be worn.

8.2.3 Environmental exposure controls

Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Do not allow the material to interfere with water pipes, lacrimation and soil.



TÜRBİN YAĞI 150

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

Date of First Publication: 20.12.2003Revision Date: 28.11.2020Revision Number: 07SDS Number: KG-F-244

Page 5 of 9

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	: Clear, Liquid	
Colour	: Amber	
Odour	: Characteristic	
Odour Threshold	: Data not available	
рН	: Not applicable	
Melting Point	: Not applicable	
Pour Point	: -9 'C	
Initial boiling point and boiling range : Data not available		
Flash Point 'C	: 240 'C (Method: ASTM D92, Cleveland open cup).)	
Evaporation Rate	: Data not available	
Flammability (solid, gas)	: Data not available	
Upper / Lower Flammability Limits: Data not available		
Vapour Pressure	: Data not available	
Vapour Density	: Data not available	
Density, 15'C	: 0.90 g/ml	
Solubility in Water	: Negligible	
Partition Coefficient	: Data not available	
Auto-ignition Temperature	: Data not available	
Decomposition Temperature : Data not available		
Viscosity 40'C	: 150 mm ² /s (Method: ASTM D445)	
Explosive properties	: Data not available	
Oxidizing properties	: Data not available	



TÜRBİN YAĞI 150

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

Date of First Publication: 20.12.2003Revision Date: 28.11.2020Revision Number: 07SDS Number: KG-F-244

Page 6 of 9

9.2 Other information

Data not available

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

See-sub-sections below

10.2 Chemical stability

Stabile

10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, no hazardous reactions will occur.

10.4 Conditions to avoid

Do not expose to high temperatures or direct sunlight.

10.5 Incompatible materials

Ayoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

Thermal decomposition products will vary with conditions. If there is not a complete combustion , smoke, hazardous gases, including carbon dioxide and carbon monoxide occurs.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Eye contact	: May irritate eyes.
-------------	----------------------

Skin contact : May cause skin irritation.

- **Ingestion** : May cause discomfort if swallowed. The main symptoms are gastrointestinal ailments, including upset stomach.
- **Inhalation** : May cause irritation to eyes, nose and throat at high vapour concentrations.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

It is thought to be harmful to aquatic organisms. Spills on the surface of water forming a film layer prevents oxygen transfer.

12.2 Persistence and degradability

Expected to be inherently biodegradable.



TÜRBİN YAĞI 150

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

Date of First Publication: 20.12.2003Revision Date: 28.11.2020Revision Number: 07SDS Number: KG-F-244

Page 7 of 9

12.3 Bioaccumulative potential

Data not available.

12.4 Mobility in soil

Spilled product can cause pollution of groundwater.

12.5 Results of PBT and vPvB assessment

Data not available

12.6 Other adverse effects

No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Dispose of by incineration or other suitable means under conditions approved by the local authority or via licensed waste disposal contractor.

Waste no time to be spilled to the environment and waterways. Dispose of packaging or containers in accordance with local regional national and international regulations.

SECTION 14: TRANSPORT INFORMATION

14.1 UN number

Not classified as hazardous for transport (ADR/RID, ADNR, IMDG, ICAO/IATA)

14.2 UN proper shipping name

Not classified as hazardous for transport (ADR/RID, ADNR, IMDG, ICAO/IATA)

14.3 Transport hazard class(es)

Not classified as hazardous for transport (ADR/RID, ADNR, IMDG, ICAO/IATA)

14.4 Packing group

Not classified as hazardous for transport (ADR/RID, ADNR, IMDG, ICAO/IATA)

14.5 Environmental hazards

Not classified as hazardous for transport (ADR/RID, ADNR, IMDG, ICAO/IATA)

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable



TÜRBİN YAĞI 150

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

Date of First Publication: 20.12.2003Revision Date: 28.11.2020Revision Number: 07SDS Number: KG-F-244

Page 8 of 9

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Applicable EU Directives and Regulations:

Regulation (EC) No 1907/2006 - REACH Regulation No 1272/2008 – CLP (Regulation on classification, labelling and packaging) Commission Regulation (EU) 2015/830 ECHA Guidance on the compilation of safety data sheets

SECTION 16: OTHER INFORMATION

Abbreviations and acronyms

ADR ADNR	: International Carriage of Dangerous Goods by Road : Carriage of Dangerous Goods by Inland Waterways
RID	: Regulations Relating to International Carriage of Dangerous Goods by Rail
IMDG	: International Maritime Dangerous Goods
ÍCAO-TI	: International Civil Aviation Organization - Technical Instructions for the Safe Transport of
	Dangerous Goods by Air
IATA	: International Air Transport Association
ACGIH	: American Conference of Governmental Industrial Hygienists
ASTM	: American Society for Testing and Materials
CAS	: Chemical Abstracts Service
GHS	: Globally Harmonised System of Classification and Labelling of Chemicals
OEL	: Occupational Exposure Limit
TWA	: Time-Weighted Average.
STEL	: Short term exposure limit
PBT	: Persistent, Bioaccumulative and Toxic
vPvB	: very Persistent and very Bioaccumulative
MARPOL 73/78	: International Convention for the Prevention of Pollution From Ships

Wording of the H-statements in section 2 and 3:

H336	: May cause drowsiness or dizziness
H304	: May be fatal if swallowed and enters airways
H315	: Causes skin irritation
H410	: Very toxic to aquatic life with long-lasting effects
H411	: Toxic to aquatic life with long-lasting effects

Full text of other abbreviations

STOT SE 3	: Specific Target Organ Toxicity (Category 3)
Asp. Tox.	: Aspiration Toxicity
Skin Irrit.	: Skin Irritation
Aquatic Chronic	: Aquatic Chronic



TÜRBİN YAĞI 150

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

Date of First Publication: 20.12.2003Revision Date: 28.11.2020Revision Number: 07SDS Number: KG-F-244

Page 9 of 9

Revision Comments

Company title change

Issued by

Name and Surname: Arzu GÜRBIYIKContact Information: arzu.gurbiyik@oyakpetrol.com.trDocument Type: Chemical Assessment Specialist CertificateDocument Date: 06.12.2018Certificate Number: TÜV/11.06.03

Warning

The information presented about health safety and environment issues in this safety data sheet was given by considering of best knowledge and reliable sources at the date of its preparation. Although maximum effort was shown, no warranty is expressed or implied regarding the accuracy of these kdata or the results to be obtained from the use thereof.

Health and safety precautions and environmental advice noted in this data sheet may not be accurate for all individuals and/or situations.

 \mathcal{H} is the user's obligation to evaluate and use this product safety and to comply with all applicable laws and regulations.

No statement made in this data sheet shall be construed as a permission, recomendation or authorization given or implied to practise any patented invention without a valid licence.

The GÜZEL ENERJİ AKARYAKIT A.Ş. shall not be responsible for any damage or injuru resulting from abnormal use of the material from any failure to adhere to recommendations or from any hazards inherent in the nature of the material.