



# PRODUCT SPECIFICATION

# SPECIFICATION

Product Name: MOLD OIL C

PRIMARY TESTS	METHOD	SPECIFICATION		
		MIN	TYP	MAX
Appearance	Visual		Clear and Bright	
Colour	ASTM D1500 / TS 1713 ISO 2049	L 0.5	1	2
Density 15 °C, g/ml	ASTM D4052 / TS EN ISO 12185	0.830	0.85	0.885
Viscosity 40 °C, mm <sup>2</sup> /s	ASTM D445 / TS EN ISO 3104	10	20	30
SECONDARY TESTS		METHOD	SPECIFICATION	
Pour Point, °C	ASTM D97 / TS EN ISO 3016		-9	
Flash Point, °C (COC)	ASTM D92 / TS EN ISO 2592		150	

Document Code	Revision No/Date	Page No	Prepared	Checked	Approved
KG-ÜS-093	12/11.08.2025	1/1	FACTORY HSEQ & LAB. MANAGER	MANAGEMENT REPRESENTATIVE	FACTORY MANAGER

\* As the defined values are typical values, there can be some little changes according to the production. M Oil keeps all the rights to update and change the formulations of products without making any announcements. For the updated informations and technical data about the products and product packagings, please contact with M Oil.