# PRODUCT SPECIFICATION

SPECIFICATION

**Product Name:** MONOMOL SAE HD 10W EXTRA

| PRIMARY TESTS | METHOD | SPECIFICATION | | |
|---|---|---|---|---|
| | | MIN | TYP | MAX |
| Appearence | Visual | | Clear and Bright | |
| Colour | ASTM D1500 / TS 1713 ISO 2049 | 0.5 | 1 | 2 |
| Density 15 °C, g/ml | ASTM D4052 / TS EN ISO 12185 | 0.860 | 0.880 | 0.895 |
| Kinematic Viscosity 100°C, $mm^2/s$ | ASTM D445 / TS EN ISO 3104 | 5 | 6.5 | 8 |
| T.B.N. mgKOH/g | ASTM D2896 / TS ISO 3771 | 4 | | |

| SECONDARY TESTS | METHOD | SPECIFICATION | | |
|---|---|---|---|---|
| Kinematic Viscosity 40 °C, $mm^2/s$ | ASTM D445 / TS EN ISO 3104 | | 45 | |
| Viscosity Index | ASTM D2270 / TS ISO 2909 | | 100 | |
| Pour Point, °C | ASTM D97 / TS EN ISO 3016 | | | -30 |
| Flash Point, °C (COC) | ASTM D92 / TS EN ISO 2592 | 204 | | |
| Cold Cracking -25 °C, cp | ASTM D5293 / TS 1896 | | | 7000 |
| Aniline Point, °C | TS 1615 ISO 2977 | 90 | | |
| Evaporation Loss, %m/m | ASTM D5800 / TS 13489 | | | 15 |
| Predicting the Borderline Pump. Temp. °C (-30 °C) | TS 4409 | | | 60000 |
| Foaming Characteristic (II Kd.) ml/ml | ASTM D892 / TS 1834 ISO 6247 | | | 50/0 |
| Sulfated Ash %m/m | ASTM D874 / TS ISO 3987 | | | 2 |
| Copper Corrossion (100 °C, 3 hours) | ASTM D130 / TS 2741 EN ISO 2160 | | | 1b |

**PERFORMANCE LEVELS:** API : CD / SF

| Document Code | Revision No/Date | Page No | Prepared | Checked | Approved |
|---|---|---|---|---|---|
| KG-ÜS-035 | 10/28.04.2026 | 1/1 | LAB. & QUALITY SPECIALIST | MANAGEMENT REPRESENTATIVE | FACTORY MANAGER |

* As the defined values are typical values, there can be some little changes according to the production. M Oil keeps all the rights to update and change the formulations of products without making any announcements. For the updated informations and technical data about the products and product packagings, please contact with M Oil.